

Power-Kleen CI

Wash Solution Corrosion Inhibitor

Cabinet and Wash Solution Corrosion Inhibitor

Power-Kleen CI is 100% active chemical. Excellent for application not requiring detergents or normal detergents may excessively foam due to different types of greases or soils but still need to maintain the pH to prevent corrosion inside the mild washer cabinet.

ADVANTAGES

- High rinseability provides a complete chemical removal with no staining or residues.
- Contains no metallic compounds such as chromate or zinc.
- No foaming during the wash process
- Contains no silicone to interfere with new coatings or paint.
- Formulated to protect your washer & unrinsed parts including Ferrous Metals, Copper, and Aluminum.

PHYSICAL PROPERTIES

Form: Powder, Stick pr Pellet
Color: Pinkish Blue
pH (use dilution) 10.9
Storage Stability Excellent

MIXING INSTRUCTIONS

For StingRay / MART Parts Washers, heat the water to at least 160 degrees. Mixing rate of .8 per gallon for powder (30-8 oz sticks 15 lbs, will treat approximately 300 gallons) at 1200 ppm - NO₂ (Nitrite). Carefully distribute 8 oz (1 stick) of inhibitor per 10 gallons of water, on the drip pan, beneath the turntable in the StingRay / MART Parts Washer. For all other cleaning equipment, add chemical carefully and as instructed by the machine manufacturer. Avoid "dumping" of chemical directly into washer reservoir. Operate the wash cycle at 160 to 190 degrees F, to distribute chemical and mix into solution. Avoid contact with chemical and solution.

PACKAGING

Part Number	Package Size
22134	15 lbs sticks
85208	50 lbs Powder
85209	400 lbs Powder

- Shipping: Ships UPS or Truck

HEALTH AND SAFETY

Avoid contact with chemical and solution. Avoid inhaling fumes. Instructions can also be found on the Power-Kleen CI label, StingRay Tech Services Website or reference the StingRay / MART Parts Washer Operating Manual. Get the most recent MSDS from our website at www.stingrayservice.com or call StingRay Tech Services.



2450 Adie Road, Maryland Heights, MO 63043 USA
Ph 800-543-6278 Fax 314-567-6318
E-mail service@stingwash.com Website www.stingrayservice.com